

Contents

Page

Foreword	v	
9.6.2	Rotodynamic pumps for assessment of applied nozzle loads	1
9.6.2.1	Introduction	1
9.6.2.1.1	Purpose	1
9.6.2.1.2	Scope	1
9.6.2.2	Relevance of nozzle loading evaluations	1
9.6.2.2.1	Piping loads on pumps — practical insights	2
9.6.2.2.2	General nozzle loading effects on pumping equipment	4
9.6.2.3	Horizontal end suction pumps (ANSI/ASME B73.1 and B73.3)	7
9.6.2.3.1	Scope	7
9.6.2.3.2	Nomenclature and definitions	7
9.6.2.3.3	Criteria for loading allowances	8
9.6.2.3.4	ANSI/ASME B73.1 pump assessment of applied nozzle loads	9
9.6.2.3.5	ANSI/ASME B73.3 sealless pump assessment of applied nozzle loads	13
9.6.2.3.6	Nozzle load adjustment factors	13
9.6.2.4	Vertical in-line pumps (ANSI/ASME B73.2)	15
9.6.2.4.1	Scope	15
9.6.2.4.2	Nomenclature and definitions	15
9.6.2.4.3	Criteria for loading allowances	15
9.6.2.4.4	ANSI/ASME B73.2 pump assessment of applied nozzle loads	16
9.6.2.5	Axially split one- and two-stage pumps (BB1)	17
9.6.2.5.1	Scope	17
9.6.2.5.2	Definitions	17
9.6.2.5.3	Criteria for loading allowances	18
9.6.2.5.4	Axial split case pumps (single-stage double suction and two-stage single suction) assessment of applied loads	20
9.6.2.6	Vertical turbine short set pumps (VS1 and VS2)	21
9.6.2.6.1	Scope	21
9.6.2.6.2	Definitions	21
9.6.2.6.3	Methodology	22
Appendix A	Material Adjustment Factors (Normative)	27
Appendix B	Example assessments of applied nozzle loads – ASME B73.1 pumps	30

Appendix C	Example assessments of applied nozzle loads – ASME B73.2 pumps	38
Appendix D	Example assessments of applied nozzle loads – axial split case pumps (single-stage double suction and two-stage single suction)	40
Appendix E	Example assessments of applied nozzle loads – vertical turbine pumps	41
Appendix F	Methods of analysis	43
Appendix G	References	49
Appendix H	Index	51

Figures

9.6.2.2.2.3	— Example of tight running clearances between stationary and rotating components	5
9.6.2.2.2.4	— Example of nozzle load effect on alignment at coupling	6
9.6.2.3.2.2	— Coordinate system for ASME B73.1 and B73.3 horizontal end suction pumps	7
9.6.2.3.6.1.1	— Stilt-mounted baseplate	14
9.6.2.4.2.2	— Coordinate system for ASME B73.2 vertical in-line pumps	15
9.6.2.5.2	— Coordinate system for axial split case pumps	18
9.6.2.6.2a	— Nozzle loads for above pump base (floor) discharge pumps	23
9.6.2.6.2b	— Nozzle loads for below pump base (floor) discharge pumps	24
F.1	— Representation of part of a mesh of a structure with its elements and nodes	44
F.2	— Example for loads and restraints considered for analysis for an OH2 pump	45
F.3	— Devices that can be used to simulate nozzle loading: a) for moments, b) for forces and moments	47

Tables

9.6.2.2.1	— Possible problems induced by piping and corresponding mitigations	4
9.6.2.3.4a	— Equation Sets 1 through 5	10
9.6.2.3.4c	— Maximum forces and moments for use with Equation Set 2 to assess applied loads	11
9.6.2.3.4b	— Maximum forces and moments for use with Equation Set 1 to assess applied loads	12
9.6.2.3.4d	— Maximum forces and moments for use with Equation Set 3 to assess applied loads	13
9.6.2.3.4e	— Maximum forces and moments for use with Equation Set 4 to assess applied loads	13
9.6.2.4.4a	— Equation Set 6	16
9.6.2.4.4b	— Maximum forces and moments for use with Equation Set 6 to assess applied loads	17
9.6.2.5.3a	— Equation Set 7	20
9.6.2.5.3b	— Maximum forces and moments for use with Equation Set 7 to assess applied loads based on hold-down bolts	20
9.6.2.5.3c	— Maximum forces and moments for use with Equation Set 7 to assess applied loads based on nozzle stress	20
A.1	— List of material specifications as used in Table A.2 and A.3	28
A.2	— ASME B73.1 metallic pump temperature and material adjustment factors to be used on Table 9.6.2.3.4c values for both Class 150 and Class 300 flanges	29
A.3	— ASME B73.2 metallic pump temperature and material adjustment values to be used on Table 9.6.2.4.4b values for both Class 150 and Class 300 flanges	29