

Contents

Page

Foreword	vii
9.8 Pump intake design	1
9.8.1 Introduction	1
9.8.1.1 Purpose	1
9.8.1.2 Scope	1
9.8.1.3 Nomenclature, primary symbols, and units	1
9.8.2 Design objectives	9
9.8.3 Intake structures for clear liquids	11
9.8.3.1 Rectangular intakes	11
9.8.3.2 Formed suction intakes	17
9.8.3.3 Circular pump stations (clear liquids)	19
9.8.3.4 Trench-type intakes (clear liquids)	22
9.8.3.5 Tanks – pump suction	23
9.8.3.6 Suction can vertically suspended pump intakes (clear liquids)	27
9.8.3.7 Unconfined intakes (Figure 9.8.3.7)	30
9.8.4 Intake structures for solids-bearing liquids	32
9.8.4.1 General	32
9.8.4.2 Trench-type wet wells for solids-bearing liquids	35
9.8.4.3 Circular plan wet pit for solids-bearing liquids	37
9.8.4.4 Rectangular wet wells for solids-bearing liquids	38
9.8.5 Inlet bell design diameter (D)	41
9.8.5.1 General	41
9.8.5.2 Objective	41
9.8.6 Required submergence for minimizing surface vortices	44
9.8.6.1 General	44
9.8.6.2 Controlling parameters	44
9.8.6.3 Application considerations	46
9.8.7 Physical model studies of intake structures and pump suction piping	48
9.8.7.1 Need for a physical model study	48
9.8.7.2 Physical model study objectives	49
9.8.7.3 Physical model similitude and scale selection	49
9.8.7.4 Physical model study scope	51
9.8.7.5 Instrumentation and measuring techniques	52
9.8.7.6 Test plan	54
9.8.7.7 Acceptance criteria	54
9.8.7.8 Report preparation	55
9.8.8 Use of computational fluid dynamics (CFD)	55
9.8.8.1 General	55

9.8.8.2	Simulation methods	55
9.8.8.3	Unacceptable uses of CFD modeling in pump intake hydraulics	56
9.8.8.4	Acceptable uses of CFD modeling in pump suction hydraulics	56
Appendix A	Remedial measures for problem intakes	57
Appendix B	Sump volume (informative)	73
Appendix C	Intake basin entrance conditions, trench-type wet wells for solids-bearing liquids (informative)	77
Appendix D	Performance enhancements for trench-type wet wells (informative)	82
Appendix E	Aspects of design of rectangular wet wells for solids-bearing liquids (informative)	88
Appendix F	Suction bell design (informative)	94
Appendix G	Submersible turbine pumps – well motor type (informative)	96
Appendix H	Modification of existing pumping systems (informative)	97
Appendix I	Alternate formed suction intake designs (informative)	98
Appendix J	Rectangular intakes for shallow liquid source (informative)	102
Appendix K	Influence of pump operating conditions on intake design (informative)	106
Appendix L	Sediment and debris issues at surface water pump station intakes (informative)	109
Appendix M	References (informative)	112

Figures

9.8.3.1.4a	— Rectangular intake structure layout	13
9.8.3.1.4b	— Filler wall details for proper bay width	15
9.8.3.2.2	— Formed suction intake	18
9.8.3.3.1a	— Wet-pit duplex sump with pumps offset	20
9.8.3.3.1b	— Wet-pit duplex sump with pumps on centerline	20
9.8.3.3.1c	— Dry-pit/wet-pit duplex sump	20
9.8.3.3.1d	— Wet-pit triplex sump, pumps in line	20
9.8.3.3.1e	— Wet-pit triplex sump, compact	20
9.8.3.3.1f	— Dry-pit/wet-pit triplex sump	20
9.8.3.4.1	— Trench-type wet well	22
9.8.3.5.4	— Datum for calculation of submergence	25
9.8.3.5.5	— Definitions of V and D for calculation of submergence	26
9.8.3.6.4	— Open bottom suction can intakes	29
9.8.3.6.5	— Closed bottom Suction can	30
9.8.3.7	— Unconfined intakes	31
9.8.4.1.4	— Open trench-type wet well	34
9.8.4.3.1a	— Circular wet pit with sloping walls and minimized horizontal floor area (dry-pit pumps)	38
9.8.4.3.1b	— Circular wet pit with sloping walls and minimized horizontal floor area (submersible pumps shown for illustration)	39
9.8.4.3.1c	— Circular wet pit with sloping walls and minimized horizontal floor area (wet-pit pumps shown for illustration)	40

9.8.4.4.4 — Confined wet-well design	41
9.8.5.2 — Inlet bell design diameter	43
9.8.6.3 — Minimum submergence to minimize free surface vortices.	47
9.8.7.5a — Classification of free surface and subsurface vortices	53
9.8.7.5b — Typical swirl meter.	53
A.1 — Examples of approach flow conditions at intake structures and the resulting effect on velocity, all pumps operating.	59
A.2 — Examples of pump approach flow patterns for various combinations of operating pumps	60
A.3 — Comparison of flow patterns in open and partitioned sumps	61
A.4 — Effect of trash rack design and location on velocity distribution entering pump bay.	61
A.5 — Flow-guiding devices at entrance to individual pump bays.	62
A.6 — Concentrated influent configuration, with and without flow distribution devices	63
A.7 — Baffling to improve flow pattern downstream from dual flow screen.	64
A.8 — Typical flow pattern through a dual flow screen	64
A.9 — Improvements to approach flow without diverging sump walls	65
A.10 — Elevation view of a curtain wall for minimizing surface vortices	66
A.11 — Methods to reduce subsurface vortices and pre-swirl (examples i–ix)	67
A.12 — Combination of remedial corrections	68
A.13 — Dimensional guidance for pump bell diameters	69
A.14 — Tank antivortex devices	71
A.15 — Tank inflow and outflow configurations	72
B.1 — Graphical analysis for liquid-level controllers	74
B.2 — Graphical analysis for a “smart” controller	76
C.1 — Schematic diagram of approach pipe	78
D.1 — Open trench-type wet-well hydraulic jump	83
D.2 — Open trench-type wet-well with inlet baffle	83
D.3 — Suction inlet vanes	84
D.4 — Floor cone with vanes for clear liquids	84
D.5 — Floor cone with vanes for solids-bearing liquids.	85
D.6 — Flow splitter in wet well	85
E.1 — Front – high-level entry	90
E.2 — Schematic, front – high-level entry	90
E.3 — Side – high-level entry	91
E.4 — Schematic, side – high-level entry	91
E.5 — Side – low-level entry	92
E.6 — Schematic, side – low-level entry	92
E.7 — Recommended sump dimensions.	93
F.1 — Bell intake shapes	95
G.1 — Submersible vertical turbine pump	96
I.1a — Stork-type FSI, plan view	99
I.1b — Stork-type FSI, elevation view	99

I.1c — Stork-type FSI, perspective view	99
I.2a — Shoe-box-type FSI, plan view	100
I.2b — Shoe-box-type FSI, Section B	100
I.2c — Shoe-box-type FSI, Section A	101
J.1 — Configuration for rectangular intakes withdrawing from shallow liquid source, maximum three pumps (refer to Figure J.2).	104
J.2 — Pump bay details near the pump suction inlet for rectangular intakes with a shallow liquid source	105
K.1 — System with up to Three Pumps Operating in Parallel	106
K.2 — Pumps Operating in Parallel with Range of Operating Conditions	107